borg&
overström

u2

Unrivalled Performance

Solidly practical and visually striking, this innovative range brings a high capacity refreshment solution to any Horeca environment.

Key Features
- Robust, solid build quality
- Simple to operate and maintain
- Available in ambient, chilled and sparkling
- Aesthetically striking
- Compact undercounter unit
- High capacity output

Available accessories
- Sanitisation Kit
- Install Kit with Filter
- Sparkling Refill (CO_2E290) (600g)
- CO_2 Regulator with Gauge
- Large Drip Tray
- Blue Tint Cups (7oz)

Power Requirements
Hertz 50/Volts 230
Max power consumption
Cold, Ambient & Sparkling 400W
Cold & Ambient 150W

Cold Temperature
Min 2°C /Max 11°C
Throughput litres per hour
Cold 60

Dimensions	WxDxH
Undercounter	262x450x485mm
Tap Dimensions	220x250x470mm
Dispense Height	285mm

Water options

Configuration

Recommended environment

Number of users

u2 Models

Direct Chill, Complete Undercounter System, Chilled & Ambient - 601362
Direct Chill, Complete Undercounter System, Chilled & Sparkling - 601364
Direct Chill, Complete Undercounter System, Chilled, Ambient & Sparkling - 601392

Water system

Borg & Overström Direct Chill utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.

Phone
+44 (0)1362 695 006
Email
sales@borgandoverstrom.com

borgandoverstrom.com

Distributed by

Ref: 838145
Version: 02022016

GB